

BID CORRIGENDUM

**AMENDMENT NO. 01 DATED 26.02.2024 To GEM BID NO.
GEM/2024/B/4629755**

1.0 This addendum/corrigendum is issued to amend the **Technical Specifications** as under:

Item Srl No.	Material Code	Existing Specifications	Amended Specifications
10 (Thermal Well Head for 7" Casing completion for CSS Wells)	03640072	<p>Main Parts of the Wellhead:</p> <p>Section A 1. PACKOFF CC-21 11 X 7 4765 PSI RWP WITH O-RING SEALS AND BLEEDER PORT RX GASKET ONLY, API 6A XDD, PSL-2, PR2. Requirement per well head: 1 No 2. RING GASKET OVAL R-54 316 STAINLESS STEEL API 6A . Requirement per well head : 1 No. 3. CAPPING FLANGE ASSEMBLY 11 5000 STUDDED BOTTOM X STUFFING BOX FOR 7 CASING TOP 1430 psi RWP YELLOW CHROMATE ZINC PLATED STUDS AND NUTS API 6A YDD-NL PSL-2 PR1 . Requirement per well head : 1 No.</p> <p>Section B 4. TUBING HEAD 7- 1/16 5000 X 7 SOW BTM W/ TWO 2 1/16 5000 STUDDED SIDE OUTLETS W/ 1.900 VR THREAD LOCKSCREWS, WITH NECESSARY STUDS & NUTS FOR RWP AND RWT OF TUBING HEAD, 6.45" BORE 14.00" LONG 3575 PSIG WORKING PRESSURE API 6A YDD NL PSL 2 PR2, Requirement per well head: 1 No.</p> <p>6. TUBING HANGER TYPE CTC-HT 7 1/16 NOMINAL X 2-7/8 EU BOX BOTTOM X 2 7/8 EU BOX TOP WITH METAL SEAL AND 2-1/2 BPV THREAD 5.25 NOMINAL DIAMETER X 1.75 EFFECTIVE LENGTH EXTENDED NECK 5.25 DIAMETER X 5.75 LONG TONGING NECK 2.40 BORE 15.00 LONG API 6A LYDD-NL PSL-2 PR2. Requirement per well head: 1 No.</p> <p>Section C 31. PRESSURE GAUGE 0 5000 PSI DUAL SCALE (PSI / BAR) 1/2 NPT LOWER MOUNT 316SS CONNECTION 6 FACE GLYCERIN FILLED NACE MR0175. Requirement per well head: 2 Nos.</p>	<p>Main Parts of the Wellhead:</p> <p>Section A 1. DELETED 2. No change 3. No Change</p> <p>Section B 4. TUBING HEAD 7- 1/16 5000 X 7 SOW BTM W/ TWO 2 1/16 5000 STUDDED SIDE OUTLETS W/ 1.900 VR THREAD LOCKSCREWS, WITH NECESSARY STUDS & NUTS FOR RWP AND RWT OF TUBING HEAD, 3575 PSIG WORKING PRESSURE API 6A YDD NL PSL 2 PR2, Requirement per well head: 1 No.</p> <p>6. TUBING HANGER TYPE 7 1/16 NOMINAL X 2-7/8 EU BOX BOTTOM X 2 7/8 EU BOX TOP THREADS WITH METAL SEAL & HIGH TEMP. PACKING AND 2-1/2 BPV THREAD EXTENDED NECK FOR PRESSURE TESTING THE CONNECTION ALONG WITH SUFFICIENT LENGTH OF TONGING NECK API 6A LYDD-NL PSL-2 PR2. Requirement per well head: 1 No.</p> <p>Section C 31. 0-5000 PSI GUAGE 4.1/2" DIAL FACE, TAPPED FOR MALE CONNECTION (AS PER THE NEEDLE VALVE). Requirement per well head: 2 No.</p>

20 (Thermal Well Head for 9.5/8" Casing completion for CSS Wells)	03640073	<p>Section B</p> <p>4. TUBING HANGER 11" NOMINAL X 2-7/8" TOP AND BOTTOM THREADS C/W SEAL RING PREP AND 2-1/2" BPV THREADS, EXTENDED NECK WITH METAL SEAL PREP HIGH TEMP PACKING, SEALS ON EXTENDED NECK FOR PRESSURE TESTING CONNECTION, YDD-NL, PSL-2 PR2. Requirement per well head: 1 No.</p>	<p>Section B</p> <p>4. TUBING HANGER 11" NOMINAL X 2-7/8" TOP AND BOTTOM EU BOX THREADS C/W SEAL RING PREP AND 2-1/2" BPV THREADS, EXTENDED NECK WITH METAL SEAL PREP HIGH TEMP PACKING, SEALS ON EXTENDED NECK FOR PRESSURE TESTING THE CONNECTION ALONG WITH SUFFICIENT LENGTH OF TONGING NECK, YDD-NL, PSL-2 PR2. Requirement per well head: 1 No.</p>
---	----------	--	--

2.0 All the Terms & Conditions of the Bid Document remain unaltered.

sd/-
A. D. SINGH
Manager (C&P)
For General Manager (C&P)
For Executive Director (RF)